HOW TO SANITIZE RV WATER - 3/13/19

Steve & Ann Beede

- 1. Bring RV Home from storage
- 2. Drain all Tanks Faucets, tanks, low point drains
- 3. Mix 1.5 cups bleach w 10 gal of water
- 4. Use sump pump to pump bleach mixture to fresh water tank
- 5. Hook up hose to fresh water tank
- 6. Connect power
- 7. Turn on water hose
- 8. Turn on water pump
- 9. Open all faucets and water outlets until air is pushed out and bleach smell water runs
- 10. Shut faucets and water pump
- 11. Fill fress water tank from hose
- 12. Disconnect hose and electric from RV
- 13. Drive RV on swerving up & down route (circle SCLH)
- 14. Let RV sit 3-4 hours
- 15. Start draining all tanks open faucets and low point drains
- 16. Shut faucets and re-cap low drains when empty
- 17. Start flush from City water pigot
- 18. Run water until no chlorine smell w faucets open
- 19. Add water to fresh water tank Fill
- 20. Drain fresh water tank w low drain caps off
- 21. Re-cap low drains leave approx 1/4 tank
- 22. Turn on water pump
- 23. Taste fresh water for clarity if chlorine taste add vinegar
- 24. Store fill and drain hoses
- 25. Disconnect electric power
- 26. Store RV
- 23. Disconnect electricity
- 24. Taste water for chlorine